

ALPHATRUK PHILIPPINES INC.

North Diversion Service Road Pandayan 3020 City of Meycauayan Bulacan Philippines www.alphatruk.com.ph | info@alphatruk.com.ph



HOWO T7S Dump Truck 6x4 (380Ps, 20cbm)



Note: The picture is only for reference.

ENGINE						
Parameters	/ 11 \		/			
Engine Model	Rated Power (KW/RMP)	Maximum Torque (NM/RMP)	Features			
WP10.380E22	280/2200	1600/1300~1500	4 Stroke Direct Injection Diesel Engine 6 cylinder in line with coolant cooling, intercooler Turbocharged,9.726 liter			
СLUТСН	ф430 diaphragm spring clutch, single plate					
TRANSMISSION .						

TRANSMISSION			
Model	HW19710+HW50 PTO		
Туре	10 Forward Speed + 2 Reverse		
Ratio	14.284 10.623 7.871 5.876 4.375 3.265 2.428 1.799 1.343 1 13.913 3.18®		

FUFL	TANK	CAPACITY	
IOLL		CALACIII	

400

	AXLES	STEERING SYSTEM		
Steering	VGD95	Model	BOSCH	
Steering	loading capacity 9Tons/drum brake	Туре	Hydraulically assisted	
	MCX16	WHEELS & TIRES		
			WIILLES & TINES	
Driving	Double reduction loading capacity 16 Tons/drum brake	Rim	8.5-18	

	FRAME	SUSPENSION		
Material	High tensile steel	Steering Axle	leaf springs	
Section	300×80×8+8mm	Driving Axle	leaf springs	

	BRAKING SYSTEM
Туре	Air brake system
Service Brake	dual circuit compressed air brake
Parking Brake (Emergency)	spring energy, compressed air operating on rear wheels
Auxiliary Brake	engine exhaust valve brake

ELECTRICAL SYSTEM				
Туре	SINOTRUK CAN bus System with TFT instrument			
Voltage	24 V, negative grounded			
Batteries	2x12V, 105Ah			
Alternator	28V/55A			

	WEIGHT (kg)				
1	Gross Vehicle Weight			25000	
2	Gross Car Weight			N\A	

VEHICLE DIMENSIONS (mm)						
1	Wheel base			3800		
2	Maximum Driving Speed (km/h)			≈65		
3	Maximum Gradeability (%)			≈45		
4	Minimum Ground Clearance (mm)	7				
5	Overall Dimension					

 Others
 Cab T7S, One Bunk ,with A/C

 Body
 5600*2300*1500

Note: The manufacture reserves the right of technical alteration/change for better improvement without prior notice.